

logitech®

# SEE BETTER. MEET BETTER.



## Logitech Rally Camera

With premium industrial design and an Ultra-HD imaging system, Rally Camera tops the lineup of standalone video cameras from Logitech\*. Packed with advanced optics and breakthrough technology enhancements, Rally Camera delivers peerless performance, exceptional versatility, and easy deployment.

Rally Camera combines world-class Logitech optics and 4K sensor with whisper-quiet mechanical pan, tilt, and zoom functions and high-end materials

suitable for any professional setting. With razor-sharp 15X HD zoom, expansive 90° field of view, and truly phenomenal video quality, Rally Camera captures every person in the room with amazing clarity.

Logitech RightSight™ camera control\* automatically moves and adjusts the lens to comfortably frame participants in rooms of all shapes and sizes while Logitech RightLight™ technology optimizes light balance to emphasize

faces and render natural-looking skin tones, even in dim or backlit conditions.

Rally Camera offers versatile mounting and cabling options for easy installation and integrates seamlessly with existing audio infrastructure. Plus, USB plug-and-play ensures compatibility with every leading video conferencing software platform with no additional software required.

## FEATURES & BENEFITS

### Top-of-the-line stand alone PTZ video camera

Ideal for professional video collaboration in meeting spaces of any size, from conference rooms to training facilities, boardrooms, and lecture halls.

### Up to 4K Ultra-HD video quality at 30 frames per second

Rally Camera delivers HD and Ultra HD resolutions with brilliantly sharp video, outstanding color reproduction, and exceptional optical accuracy.

### Logitech RightSight™ camera control

Automatically moves and adjusts the lens to comfortably frame meeting participants in rooms of all shapes and sizes\*. Enjoy hands-free convenience or take manual control: participants are always in view and optimally pictured on-screen.

### Logitech RightLight™ technology

Whether in low light or bright sunshine/backlit conditions, RightLight technology with Wide Dynamic Range (WDR) optimizes light balance and prioritizes faces over objects and surfaces to render natural-looking skin tones.

### Firmware upgradeable

Firmware tool makes it easy to apply the latest features and enhancements.

### 90° field of view with mechanical pan (± 90°) and tilt (+50°/-90°)

Expansive 90° field of view provides a wide, distortion-free meeting scape. Enhanced, whisper-quiet PTZ motor makes moving from preset to preset a smooth operation.

**Premium Logitech-engineered glass lens**  
Large, light-gathering lens meets the highest optical standards and provides exceptional sharpness, color, speed, and resolution.

### Autofocus

Automatically ensure that people and objects are clearly in focus wherever the camera is pointed.

### RF remote control

Operate Rally Camera from anywhere in the room, no need to point the remote directly at the camera.

### 3 camera presets

Define up to three preset locations (presets 1, 2, and Home) for the camera view and return to any of them with the push of a button on the remote control.

### Plug-and-play USB connectivity

Easily connects to PC, Mac® and Chrome™ devices with no additional software required.

### Works with most video conferencing applications

Compatible with virtually any video conferencing software app, including the ones you already use.

### Multiple installation options

Set Rally Camera on a table or wall mount with included hardware. An optional VESA mount is available for installations above or below the monitor. Rally Camera includes a standard tripod thread for added flexibility.

### Upside-down mounting

Rally Camera detects when it's installed upside down and automatically corrects the image orientation and camera controls.

### 15X lossless HD Zoom

Zoom wide or zero in to clearly view people, objects, whiteboard content, and other details—even at the far end of the room.

### Kensington® security slot

Security slot accommodates anti-theft lock to help secure the camera.

## SYSTEM REQUIREMENTS

### Operating Systems

Windows® 7, Windows 8.1 or Windows 10  
Mac OS X® 10.10 or higher  
Chrome OS

### Resolutions higher than 1080p

Windows 8.1 or higher or Mac OS 10.10 or higher  
USB 3.0 port and Type C cable  
Compatible software

## ADDITIONAL SOFTWARE

### \*RightSight automatic camera control

Future Availability: RightSight will be enabled by a software download, with initial support for Windows 10.

Please see [www.logitech.com/rallycamera](http://www.logitech.com/rallycamera) for information about availability and OS support.

## INSIDE THE BOX

Rally Camera  
Remote control  
USB 3.0 Type-C cable  
Power adapter with regional plugs  
Power splitter & case  
Camera mount with mounting hardware  
Documentation

## PRODUCT DIMENSIONS

### Rally Camera

Height x Width x Depth:  
7.19" x 5.88" x 5.88"  
182.5 mm x 152 mm x 152 mm

### Rally Camera Mounting Bracket

Height x Width x Depth:  
3.47" x 4.33" x 6.69"  
88 mm x 110 mm x 170 mm

### Rally Camera Power Splitter

Height x Width x Depth:  
0.84" x 3.19" x 2.38"  
21.4 mm x 81 mm x 60.5 mm

### USB 3.0 cable

7.2 ft (2.2 m)

### Power Adapter Cable

9.8 ft (3 m)

## COMPATIBILITY

UVC/plug-and-play compatible with virtually any cloud-based video conference application

Certified for Skype® for Business and ready for Teams

Cisco® Compatible

Compatible with Google® Hangouts Meet, Zoom, BlueJeans, BroadSoft, GoToMeeting™, Vidyo, and other video conferencing, recording, and broadcasting applications that support USB cameras

## SPECIFICATIONS

Part#: 960-001226

UPC: 097855140234

### Camera

Ultra-HD imaging system supports:  
◦ 4K, 1440p, 1080p, 900p, 720p, and most SD resolutions at 30 fps  
◦ 1080p, 720p at 30 fps and 60 fps  
Smooth motorized pan, tilt and zoom

Pan: ±90°

Tilt: +50 / -90

15x HD zoom

90° field of view

Autofocus

3 camera presets

Kensington security slot

Video mute/unmute LED indicator

Standard tripod thread

### RightSense™ Technologies

RightLight with Wide Dynamic Range (WDR)  
RightSight automatic camera control

### Remote Control

RF remote control (line of sight not required)  
CR2032 battery (included)

### Power

AC Power adapter with regional plugs  
Power cable (9.8 ft/3 m)

### Mount

Invertible wall mount with power splitter bay and cable management

## CONNECTIVITY

USB Type-C  
MIPI Connector  
Expansion Slot

## WARRANTY

2-Year Limited Hardware Warranty

## SOFTWARE DOWNLOADS

Required software: None  
Optional Camera Settings App gives access to advanced options: